

COBRA™

S E R I E S



COBRA™

The New Way® Cobra™ is the contractor's choice with its outstanding compaction in a lightweight 20 yd³ body. Add in the Cobra's large 3 yd³ hopper, available in 9 to 25 yd³ capacities, and a variety of container handling options, and you'll understand why the Cobra™ is setting the standard in the industry.



Proudly USA Made



A Product of **Scranton Mfg. Co., Inc.** · 101 State Street · Scranton, IA 51462 · T 800 831 1858 · F 712 652 3399 · www.newwaytrucks.com

COBRA™ SPECIFICATIONS

GENERAL SPECIFICATIONS (STANDARD)

Model	9 RL	11 RL	13 RL	16 RL	18 RL	20 RL	25 RL
Body Capacity	9 yd ³	11 yd ³	13 yd ³	16 yd ³	18 yd ³	20 yd ³	25 yd ³
Body Width (A)	82"	96"	96"	96"	96"	96"	96"
Body Length (B)	191.5"	191.5"	209.5"	212.5"	227"	244.5"	270"
Body Height (C)	71"	71"	71"	83"	83"	83"	94"
*Approx. Body Weight	9,290 lbs.	9,650 lbs.	10,012 lbs.	10,323 lbs.	10,760 lbs.	11,227 lbs.	12,200 lbs.
Hopper Capacity	2 yd ³	2.5 yd ³	2.5 yd ³	3 yd ³	3 yd ³	3 yd ³	3 yd ³
Hopper Opening Width	60"	74"	74"	74"	74"	74"	74"
Hopper Load Height	Frame	Frame	Frame	Frame	Frame	Frame	Frame
Hopper Cycle Time (sec)	26-30	26-30	26-30	26-30	26-30	26-30	26-30

HYDRAULIC CYLINDER SPECIFICATIONS (STANDARD)

Model	9 RL	11 RL	13 RL	16 RL	18 RL	20 RL	25 RL
Slide Cylinders (2)	4"	4"	4"	4.5"	4.5"	4.5"	4.5"
Sweep Cylinders (2 Each)	5"	5"	5"	5"	5"	5"	5"
Tailgate Cylinders (2 Each)	3.5"	3.5"	3.5"	4"	4"	4"	4"
Ejection Cylinder (Telescopic)	3 Stage 5.5"	3 Stage 5.5"	4 Stage 6.5"	4 Stage 6.5"	4 Stage 6.5"	4 Stage 6.5"	4 Stage 6.5"

MINIMUM CHASSIS SPECIFICATIONS (STANDARD)

Model	9 RL	11 RL	13 RL	16 RL	18 RL	20 RL	25 RL
**Minimum GVWR	23,000 lbs.	27,500 lbs.	29,000 lbs.	31,000 lbs.	33,000 lbs.	33,000 lbs.	56,000 lbs.
Recommended Cab	84"	84"	102"	112"	120"	138"	156"

*Approximate Body Weight empty and exclusive of options

**Any Chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted.
(Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)

BODY CONSTRUCTION (High Tensile Steel)

- Roof	10 GA	80K GR
- Sides	10 GA	80K GR
- Floor (sides)	10 GA	80K GR
- Floor (center)	1/4"	50K GR
- Ejection Panel	10 GA	50K GR
- Sweep Panel	1/4"	50K GR
- Tailgate (upper)	10 GA	50K GR
- Tailgate (lower)	7 GA	50K GR
- Hopper Floor (back)	1/4"	100K GR
- Slide Panel	7 GA	50K GR
- Hopper Floor	1/4"	50K GR

HYDRAULIC SYSTEMS

	US	Metric
- Oil Reservoir	40-45 gal	151-170 L
- Min. Accept. Oil Flow	20 GPM	76 LPM
- Oil Flow w/std Pump	29 GPM	110 GPM
- Max. Oper. Pressure	2,000 PSI	13,790 KPA

All models and specifications subject to change.

Visit us online at newwaytrucks.com for the latest updates.

HYDRAULIC SYSTEMS (Cont.)

- Engine RPM for STD GPM	1,200-1,500
- Hydraulic Hoses	4 to 1 Burst
- Hydraulic Filter	10 micron

STANDARD EQUIPMENT

- Semi Automatic Cycling
- Auto Back Pack
- Accelerator Kit
- Auto-Lock Tailgate
- Back Up Alarm
- All LED Lights
- Hydraulic Tank Temperature Gauge
- Right Side Hydraulic Tank Access Port
- ICC Lights and Reflectors
- Sight Gauge on Oil Tank
- Oil Pressure Gauge
- Chrome Cylinders
- Side Access Door
- Driver Alert Buzzer
- Tailgate Ajar Indicator
- Light Bar
- Bolt on Steps on Rear
- Prime Paint
- Pump
- Color Rear Vision Camera System

OPTIONAL EQUIPMENT

- Special Lighting
- PTO
- Finish Paint-Imron Elite
- Container Lifts
- Pack at idle
- Hopper Liners
- Magnum Steel Package
- Scale System
- CNG Powered

AUTHORIZED DEALER



A Product of **Scranton Mfg. Co., Inc.** · 101 State Street · Scranton, IA 51462

T 800 831 1858 · F 712 652 3399 · www.newwaytrucks.com